

Le, Hong Ha

**A model for manpower relocation considering
the impact derived from weather forecasts**

Schriftenreihe der Professur Baubetrieb und Bauverfahren

Band 31

BAUHAUS
UNIVERSITÄTSVERLAG

Copyright VDG-Weimar

Alle Rechte, auch des auszugsweisen Nachdruckes, der auszugsweisen oder vollständigen Wiedergabe, der Speicherung in den Datenverarbeitungsanlagen und der Übersetzung, vorbehalten.

Bauhaus-Universität Weimar, Professur Baubetrieb und Bauverfahren

Satz und Gestaltung: Hong Ha Le

Druck: Schätzl-Druck

ISBN: 978-3-95773-161-6

Bauhaus-Universitätsverlag Weimar als Imprint von VDG-Weimar 2014

Dissertation

zur Erlangung des akademischen Grades

Doktor-Ingenieur (Dr.-Ing.)

an der Fakultät Bauingenieurwesen
der
Bauhaus-Universität Weimar

vorgelegt von

M.Sc. Le, Hong Ha
aus Vietnam

Gutachter:

1. Prof. Dr.-Ing. Hans-Joachim Bargstädt
2. Prof. Dr.-Ing. Detlef Heck
3. Prof. Dr. Makarand Hastak

Weimar, 2014

Preface from the editor

It is only a few years ago, the computational tools and abilities still did not allow to assist in the organisation of complex construction sites, although the theoretical ideas had been quite advanced. Now Hong Ha Le has taken up on the issue of site organisation with a special focus on the weather-dependent resource allocation.

First of all a thorough resource allocation requires a detailed description of work processes. Then, on the basis of the considered parameters such as performance ratios, material and space requirements, different simulation and sensitivity analyses can be performed.

In this dissertation the author has focused on the dependencies of construction process on the weather conditions. Medium-range weather forecasts nowadays can be sufficiently precise and reliable. So it is possible to adjust the on-site work concept for an upcoming week in order to avoid unnecessary disruptions due to bad weather.

This concept is especially interesting for specialized construction companies which work with small and flexible work crews, for example for the outer lining of industrial facilities such as gasoil tanks. Companies in this field usually manage several construction projects, which are at far distance to each other and largely depend on the weather conditions.

The weather conditions concerning wind, humidity, temperature and rainfall can be very different from site to site. In order to optimize the performance, a company can allocate a more or less number of crews to each site depending on the forecasted weather in that region. Thus it can avoid idle time of crew members, but still keep a minimum of work force for auxiliary and off-site work.

The author has developed an innovative method to incorporate weather forecast information into a discrete event simulation model. In the first step, the impact of weather on the intended schedule is calculated. Then, in the second step, different allocation alternatives are offered, so that crew can be shifted from site to site.

Although this concept could also be operated on a day-to-day basis, in reality, it proves to be most attractive when operated on a weekly basis. At 75 %, the 7-day-forecast is already reliable enough to be used for crew disposition. And the company managers can now decide at the end of a week (Friday or Saturday), where to send which number of crew for the whole or for parts of the next week.

The dissertation shows that improvements and considerable innovation can be developed by combining the latest advancements in different disciplines, here in construction simulation and weather forecast algorithms.

Weimar, April 2014

Acknowledgement

I would like to express my gratitude to all those who gave me the possibility to complete the thesis.

First and foremost, I am deeply indebted to my supervisor Prof. Dr.-Ing. Hans-Joachim Bargstädt at the Bauhaus-Universität Weimar for awakening my interest and giving me opportunity to do the research in the Institute of Construction Engineering and Management. I have benefited greatly from many discussions with him, which raised new initiatives for my research. His support, valuable suggestions together with brainstorming helped me in all the time of research for and writing of this thesis.

I am grateful to Prof. Dr.-Ing. habil. Rolf Steinmetzger for his provision of useful books and information. I am beholden to Dr. Amir Elmahdi and M.Sc. Trang Dang for many discussions during the research process as well as their comments and suggestions during the writing process. My gratitude is extended to all my colleagues of the Institute of Construction Engineering and Management for their support and encouragement in my work.

I am obliged to Ms. Maureen Anderson, who looked closely at the thesis for correction and suggestions of English style and grammar.

I would like to thank also Prof. Dr.-Ing. Markus König and Dr.-Ing. Ulrike Beißert for their great help to my research. Thanks to their specific instructions of the Tecnomatix Plant Simulation program, I could faster finish the programming part of my research.

Grateful acknowledgement is made to the Ministry of Education and Training (MoET) of Vietnam and the German Academic Exchange Service (DAAD) for their funding which enabled me to stay and carry out my research in Germany. I also heartily thank to the Bauhaus-Universität Weimar for providing me the graduation scholarship in the period of three months.

In addition to all above, I would like to give my special thanks to my parents for their encouragements and support in my life and study. I would like to thank to my parents-in-law for their understanding and support. Many thanks also go to my relatives and friends for their encouragements. Finally, I express my gratitude and appreciation to my husband and my daughter for their love, patience and support.

Hong Ha Le

Weimar, April 2014

Table of Contents

Table of Contents.....	I
Abbreviations.....	IV
1 Introduction.....	1
1.1 General introduction.....	1
1.2 Motivation.....	1
1.3 Research objective.....	3
1.4 Structure of dissertation.....	3
2 State of the art in project control and weather effects.....	5
2.1 Causes of project delays.....	5
2.2 Project control.....	7
2.2.1 Control procedure.....	7
2.2.2 Control actions.....	9
2.3 Project planning and control techniques.....	11
2.3.1 Traditional techniques.....	11
2.3.2 Simulation.....	11
2.4 Literature review of weather in construction.....	13
2.4.1 Weather conditions and labour productivity.....	13
2.4.2 Impact of weather conditions on particular construction projects.....	14
2.4.3 Consideration of weather in construction contracts.....	17
2.5 Conclusion.....	18
3 Weather forecast and weather impact cases.....	20
3.1 Weather forecast.....	20
3.1.1 Forecasting methods.....	20
3.1.2 Accuracy of weather forecasts.....	20
3.1.3 Forecasting services.....	25
3.2 Weather impact cases.....	27
3.3 Interruption of construction process.....	28
3.3.1 Health hazards and work safety.....	28
3.3.2 Technical requirements of construction activities.....	31
3.4 Reduction of labour productivity.....	33
3.4.1 Definition of labour productivity.....	33
3.4.2 Influence of weather parameters on labour productivity.....	33
3.4.3 Reduction of labour productivity.....	35

3.5	Operation incapacity of construction equipment	39
4	Constraint-based simulation	41
4.1	Constraint Satisfaction Problems	41
4.2	Construction constraints	41
4.3	SIMoFIT and STS	43
4.4	Constraint-based simulation	43
4.4.1	Construction process attributes	43
4.4.2	STS Components.....	46
4.4.3	Data generation	48
4.4.4	Simulation concept.....	50
5	Simulation of forecasting weather effects on the construction process.....	52
5.1	Overview of the concept	52
5.1.1	Application of the module.....	52
5.1.2	Concept of the module	52
5.2	Process data	53
5.3	Weather forecast data	55
5.4	Data for weather impact cases.....	56
5.4.1	Interruption of construction process.....	56
5.4.2	Reduction of labour productivity	59
5.4.3	Operation incapacity of crane	62
5.5	Simulation concept.....	62
5.5.1	Weather constraints.....	62
5.5.2	Simulation of construction process considering weather constraints ...	63
5.5.3	Generation of weather parameters	66
5.5.4	Checking of weather constraints	67
5.6	Assessment of the weather-impacted schedule	71
6	Relocation of manpower	72
6.1	Introduction	72
6.2	Interaction between MAM and WCM	74
6.3	What-if scenarios.....	75
6.4	Input data.....	77
6.5	Allocation alternatives.....	78
6.5.1	Formalization	78
6.5.2	Generation of allocation alternatives for the look-ahead schedule	80
6.5.3	Generation of allocation alternatives for each allocation event	83

6.6	Calculation of allocation parameters.....	86
6.7	Evaluation of allocation alternatives.....	91
7	Application example.....	92
7.1	Overview of application example.....	92
7.2	Introduction to the construction process.....	92
	7.2.1 Construction process.....	92
	7.2.2 Dependence of the process on weather conditions.....	94
7.3	Introduction of three construction projects.....	95
	7.3.1 Construction projects.....	95
	7.3.2 Process status.....	96
	7.3.3 Manpower and working time on sites.....	97
7.4	Simulation components of Weather Construction Module.....	99
7.5	Process input data.....	100
7.6	Weather data.....	102
	7.6.1 Weather forecast data.....	102
	7.6.2 Impact cases.....	102
	7.6.3 Input data through the component <i>Weather</i>	104
7.7	Results of the Weather Construction Module.....	108
	7.7.1 Construction project in Bremen.....	108
	7.7.2 Construction project in Eisenach.....	109
	7.7.3 Construction project in Dresden.....	111
7.8	Relocation of manpower.....	112
	7.8.1 Input data.....	112
	7.8.2 Input data through Manpower Allocation Module.....	113
	7.8.3 Resulting allocation alternatives.....	114
	7.8.4 Evaluation of allocation alternatives.....	117
7.9	Conclusion.....	120
8	Conclusion and outlook.....	121
8.1	Conclusion.....	121
8.2	Outlook.....	123
	List of Figures.....	125
	List of Tables.....	127
	References.....	128
	Appendix.....	140
	Appendix A: Weather data.....	141
	Appendix B: Manpower allocation results.....	147

Abbreviations

Abbreviations	Explanation
CPM	Critical Path Method
CSP	Constraint Satisfaction Problem
DWD	German Meteorological Service
e.g.	for example
EIFS	Exterior Insulation and Finishing Systems
FSG	Flensburger Schiffbau Gesellschaft mbH & Co. KG (Flensburg Shipyard Company mbH & Co. KG)
i.e.	that is
ID	Identification number
K	Kelvin
LoB	Line-of-Balance
MAM	Manpower Allocation Module
NECA	National Electrical Contractors' Association
PERT	Program Evaluation and Review Technique
PF	Productivity factor
PF ^c	Cumulative productivity factor
PLM	Product Lifecycle Management
PR	Performance ratio
RMSE	Root Mean Squared Error
RV	Reduction of error variance
SimCoMar	Simulation Cooperation in Maritime Industries
SIMoFIT	Simulation of Outfitting Processes in Shipbuilding and Civil Engineering
STS	Simulation Toolkit for Shipbuilding
WCM	Weather Construction Module
WCT	Wind Chill Temperature index
WS	Work step

1 Introduction

1.1 General introduction

Construction planning is complicated and time-consuming work because of the dynamic and complex nature of a construction process. Contractors usually face problems of project delays and cost overruns. Hence, the issues of estimating and meeting the construction time frame are often emphasised in every contract. In fact, it is difficult to estimate the exact duration of the construction process in the planning phase because there are many unforeseeable or unexpected factors that can affect the execution process. The deviation between the actual schedule and the planned schedule happens due to many reasons such as weather effects, incorrect planning, technical problems, poor procurement decisions, etc. That is to say, construction processes normally face many uncertainties that need to be handled during the execution phase in order to complete the project on time. Therefore, making a construction project schedule prior to construction is actually not the end of the planning process. Control and further steering of the project are indeed necessary.

Detecting the deviations of the actual schedule from the planned schedule and solving the problems arising therefrom are necessary in a project control procedure. However, knowing about deviations and solving them after they have occurred seems to be a responsive action. The ability to be aware of problems, forecast their consequences before they happen and perform control actions on time is indeed quite important from the perspective of a contractor. As a result, the demand of management tools that are able to support contractors in predicting the impact of influencing factors on execution process has emerged.

Since its first development, simulation has been implemented in many research fields such as engineering, physics, social science etc. Over time, it has proved to be a powerful technique that is highly recommended for use in the field of construction management thanks to the abilities to solve many problems in construction processes. A simulation model allows users to abstract the real construction process along with its influencing factors. Furthermore, by performing simulation experiments, users can also determine appropriate solutions for problems caused by those factors.

1.2 Motivation

Weather conditions are among the many and most common causes of disruptions in the execution progress. Three sources of variability in task completion time are: the task itself, the workers performing the task, and the environment where the task is performed [1, p. 625]. Construction activities are normally executed in an outdoor environment; hence,